

CMB-67G-01

- Mini-ITX barebone system support 2nd generation Intel® Core™ i7 / i5 / i3 desktop processor
- Support one PCI-Express X16 slot , HD Audio
- VGA , DVI , 2 x Intel® Giga LAN , COM , USB



Form Factor	Mini-ITX Barebone system
Construction	Heavy-Duty steel
Processor	Support 2 nd generation Intel® Core™ i7 / i5 / i3 in LGA1155
Chipset	Intel® Q67 Express Chipset
Memory	Two DDR3 1066/1333 DIMM up to 16 GB
Drive Bay	one internal 3.5" HDD or 2 x internal 2.5" HDD space or two external 2.5" HDD space by drive cage
Extensive slot	One PCI-Express X16 slot. (Not all the PCIe cards could be fitted duo to internal physical issue)
System Fan	One 6 cm system cooling Fan
Front Panel	Power on switch , LED for Power On/Off and HDD activity 2 x USB ports , Mic-in / Ear phone
Rear Side I/O	PS/2 Key/Mouse, 2 x RJ45 LAN, 4 x USB 2.0, 1 x RS232/422/485, 2 x RS232 1 x VGA, 1 x DVI, 1 x Audio, 1 x SPDIF Reserve 2 x DB9 COM port holes (Can't be used when install 3.5" HDD or 2.5" external driver bay))
Power supply	250 Watt (AC 100 ~ 240V)
Environment	Operating Temperature: 0 ~ 40°C . Humidity: 10 ~ 85% @ 40°C (non-condensing)
Dimension	220 x 300 x 80 mm (L x W x H)

Ordering Code

CMB-67G-01	Barebone system with LV-67G , CPU cooler Fan , 250 Watt power supply & 1 x PCIe riser card
Processor	Intel® Core™ i7-2600 / i5-2400 / i3-2120 LGA 1155 desktop processor
Memory	DDR3 1066/1333 for 1.0 GB / 2.0 GB / 4.0 GB
Drive cage	Support External 2 bay 2.5" Mobile Rack

Taiwan Commate Computer Inc.

8F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

FAX: +886-2-26963911

Website: www.commell.com.tw

E-mail: info@commell.com.tw



Stage For Your Success