

PCI Video Capture Card

H.264 Hardware compression

SP-601H2

16-ch Video & Audio inputs

Support call monitor function

Scode DVR program or Completed

Demo program with SDK



Form Factor	PCI		
Compression Format	H.264 and MJPEG H/W compression (support Multi-streams: H.264 x2 + MJPEG x1)		
Video	Inputs	16-channel	
	Outputs	1 x Composite	
	Resolution	CIF, 2 CIF & D1	
	Display Rate	NTSC : 480 fps	PAL : 400 fps
	Recording Rate	NTSC	PAL
	16-ch : Total 480 fps / CIF Total 180 fps / D1	16-ch : Total 400 fps / CIF Total 150 fps / D1	
Audio	Inputs	16-channel	
	Output	1 x Composite	
OS Support	Windows XP, Linux		
Software	Windows SDK, Linux SDK		
Internal I/O	1 x 16-Channel Sensor input, 1 x 4-Channel Alarm output, 1 x 16-Channel Audio input		
External I/O	1 x D-Sub25 Video input, 1 x RCA Video output, 1 x RCA Audio output		
Cable kit	1 x 16-Channel Video input (BNC connector) Cable 1 x 20 pin header D-SUB 25 Cable (Optional) 1 x 16-Channel Audio input (RCA connector) Cable (Optional)		
Dimensions (L x W)	146mm x 95mm		

Ordering Code

SP-601H2	16-Channel H.264 Video & Audio PCI capture Card with SDK provided
SP-601H2A	16-Channel H.264 Video & Audio PCI capture Card with Scode DVR program

For further product information please visit the website at <http://www.commell.com.tw>

Taiwan Commate Computer Inc.

19F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

FAX: +886-2-26963911

Website:www.commell.com.tw

E-mail:info@commell.com.tw