

# DC-PD

---

## PoE+ Module

### User's Manual

Edition 1.81

2025/01/10



---

**Copyright**

Copyright 2018, all rights reserved. This document is copyrighted and all rights are reserved. The information in this document is subject to change without prior notice to make improvements to the products.

This document contains proprietary information and protected by copyright. No part of this document may be reproduced, copied, or translated in any form or any means without prior written permission of the manufacturer.

All trademarks and/or registered trademarks contained in this document are property of their respective owners.

**Disclaimer**

The company shall not be liable for any incidental or consequential damages resulting from the performance or use of this product.

The company does not issue a warranty of any kind, express or implied, including without limitation implied warranties of merchantability or fitness for a particular purpose.

The company has the right to revise the manual or include changes in the specifications of the product described within it at any time without notice and without obligation to notify any person of such revision or changes.

**Trademark**

All trademarks are the property of their respective holders.

---

Any questions please visit our website at <http://www.commell.com.tw>

**Packing List:**

Please check the package content before you starting using the board.



1 x DC-PD-5V/12VT




or

1 x DC-PD-5V/12VR

1 x DC Output Power Cable  
(OALDC-DC3/1040614)**Accessories for DC-PD-5V/12VR-02**

1 x MPX-350

1 x CN\_LAN Cable  
(OALPOE-02/1040628)1 x Adapter LAN Cable  
(OALGLAN-A-20 / 1040617)1 x Single LAN Adapter  
(BADPGLAND\_A / 4120007011)**Accessories for DC-PD-5V/12VR-03**

1 x MPX-210D

1 x CN\_LAN Cable  
(OALPOE-03/1040629)

1 x Driver CD



1 x Driver CD

## 1. <Product Specification>

### Product Description

Interface	RJ45 for connecting with PSE Internal 12-pin head for connecting with <a href="#">MPX-350</a> or <a href="#">MPX-210D</a> Internal 2-pin terminal block for DC input of powered board
Accessories	OALPOE-02 and OALPOE-03 for <a href="#">MPX-350</a> or <a href="#">MPX-210D</a> OALDC-DC3 for DC output
Dimensions (L x W )	84.05mm x 40.00mm

### Operating Conditions


Power Requirement	<b>T</b> series DC Input voltages from 37V to 57V <b>R</b> series from Power Sourcing Equipment
Temperature	Operating within -40°C ~+85°C Storage within -40°C ~+85°C

### Ordering Code


DC-PD-5V <b>T</b>	DC to DC, with Terminal Block, DC Input 37~57V, DC Output 5V / 7A
DC-PD-5V <b>R</b>	Compliant IEEE802.3at/af, and LTPoE++™ 90W with RJ45 connector, DC Output 5V / 7A
DC-PD-5V <b>R</b> -02	Same as DC-PD-5V <b>R</b> , with MiniPCIe <a href="#">MPX-350</a>
DC-PD-5V <b>R</b> -03	Same as DC-PD-5V <b>R</b> , with MiniPCIe <a href="#">MPX-210D</a>
DC-PD-12V <b>T</b>	DC to DC, with Terminal Block, DC Input 37~57V, DC Output 12V / 6A
DC-PD-12V <b>R</b>	Compliant IEEE802.3at/af, and LTPoE++™ 90W with RJ45 connector, DC Output 12V / 6A
DC-PD-12V <b>R</b> -02	Same as DC-PD-12V <b>R</b> , with MiniPCIe <a href="#">MPX-350</a>
DC-PD-12V <b>R</b> -03	Same as DC-PD-12V <b>R</b> , with MiniPCIe <a href="#">MPX-210D</a>

## 2. < Block Diagram >


### 2.1 <DC-PD-5V/12VR>




## 2.2 &lt;DC-PD-5V/12VT&gt;



## 3. &lt; Mechanical Drawing &gt;



## 4. &lt; Connector Location and Reference &gt;



Connector	Function
CN_LAN	12-pin Ethernet Connector
RJ45	RJ-45 LAN Port
54V_IN	2-pin power input with Terminal Block
DC_OUT	2-pin power output with Terminal Block

## 4.1 &lt;Power Input&gt;

**Note : DC input used by T series modules**

Connector : 54V\_IN

Pin	Description	Pin	Description
1	GND	3	Power input




## 4.2 <Power Output>

Connector : DC\_OUT

Pin	Description	Pin	Description
1	GND	3	Power output

For DC-PD-5V , with **+5V / 7A** Output

For DC-PD-12V , with **+12V / 6A** Output



## 4.3 <PoE Input>

LAN Connector: RJ45

Pin	Description	Pin	Description
1	MI0+	2	MI0-
3	MI1+	4	MI2+
5	MI2-	6	MI1-
7	MI3+	8	MI3-
9	LINKLED	10	ACTLED
11	LINK100	12	LINK1000
13	GND	14	GND




12 1

Connector: CN\_LAN (Part number: 53047-1210 or equivalent)

Pin	Description	Pin	Description
1	ACTLED	2	LINK0
3	RTD0+	4	RTD0-
5	RTD1+	6	RTD1-
7	RTD2+	8	RTD2-
9	RTD3+	10	RTD3-
11	LINK1H	12	LINK1G


## 5. < DC-PD T-series Installation Guide >

1. Check your 54V power supply works correctly.
2. Connect 54V power supply to 54V\_IN connector, and then DC\_OUT is 12V if you use DC-PD-12VT



## 6. < DC-PD R-series Installation Guide >

1. Check your Power Sourcing Equipment (PSE) works correctly
2. Connect MPX-350 / MPX-210D to DC-PD with CN\_LAN cable  
(There are LAN ports in MPX-350.Put the CN\_LAN cable into CN\_LAN1 or CN\_LAN2, the other for LAN adapter.)



3. Put MPX-350 or MPX-210D into motherboard.
4. Connect your PSE device to DC-PD with RJ45 cable, and then the DC\_OUT is 12V if you use DC-PD-12VR.



## Contact information

Any advice or comment about our products and service, or anything we can help you please don't hesitate to contact with us. We will do our best to support you for your products, projects and business.

### Taiwan Commate computer Inc.

Address	19F., NO.94, Sec. 1, Xintai 5 <sup>th</sup> Rd., Xizhi Dist., New Taipei City 22102, Taiwan.
TEL	+886-2-26963909
Website	<a href="http://www.commell.com.tw">www.commell.com.tw</a>
E-mail	<a href="mailto:info@commell.com.tw">info@commell.com.tw</a> (General information) <a href="mailto:tech@commell.com.tw">tech@commell.com.tw</a> (Technical Support)

Commell is a brand name of Taiwan Commate computer Inc.